Revision: 04.10.2021



Safety data sheet complying with Regulation 1907/2006/EC (REACH Regulation), EU 2020/878 and Regulation No 1272/2008/EC (CLP)

Printing date 04.10.2021

Version number 3 (replaces version 2)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: LAVA 20 CLEAR TOP COAT

UFI: GUE0-R0FC-F00T-A3CH

1.2 Relevant identified uses of the substance or mixture and uses advised against Professional use Application of the substance / the mixture: Waterproofing coating

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

OWL WATERPROOFING SOLUTIONS

135, Slaney Road, Dublin Industrial Estate

Glasnevin, Dublin 11 Tel: +353 01 830 2250

Email: info@owlwaterproofing.co.uk Website: www.owlwaterproofing.co.uk 1.4 Emergency telephone number:



European Emergency Tel.: +353 01 830 2250

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation EC No 1272/2008 CLP:



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

H373 May cause damage to organs through prolonged or repeated exposure. STOT RE 2

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

H315 Causes skin irritation. Skin Irrit. 2

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3

H335 May cause respiratory irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 2)

Printing date 04.10.2021 Version number 3 (replaces version 2) Revision: 04.10.2021

Trade name: LAVA 20 CLEAR TOP COAT

(Contd. of page 1)

2.2 Label elements

Labelling according to Regulation EC No 1272/2008 CLP:

The product is classified and labelled according to the CLP regulation.

Hazard pictograms:







GHS02 GHS07 GHS08

Signal word: Danger

Hazard-determining components of labelling:

Reaction mass of ethylbenzene and m-xylene and p-xylene

1,6-hexanediyl-bis(2-(2-(1-ethylpentyl)-3-oxazolidinyl)ethyl)carbamate

3-Isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate, oligomers

3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

Hazard statements:

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

P302+P352 IF ON SKIN: Wash with plenty of water and soap.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

(Contd. on page 3)

Printing date 12.10.2021 Version number 5 (replaces version 4) Revision: 12.10.2021

Trade name: LAVA 20 CLEAR TOP COAT

(Contd. of page 2)

P308+P313 IF exposed or concerned: Get medical advice/attention.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

Additional information:

EUH204 Contains isocyanates. May produce an allergic reaction.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable. **vPvB:** Not applicable.

	2 Mixtures escription: Mixture: consisting of the following components. egredients according Regulation (EU) 2020/878:			
EC number: 905-562-9 Reg.nr.: 01-2119488216-32-XXXX	Reaction mass of ethylbenzene and m-xylene and p-xylene Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 3, H412	25-50%		
CAS: 9016-87-9	diphenylmethane diisocyanate,isomeres and homologues Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; ↑ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5 % Skin Irrit. 2; H315: C ≥ 5 % Resp. Sens. 1; H334: C ≥ 0.1 % STOT SE 3; H335: C ≥ 5 %	10-25%		
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29-XXXX	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226	10-25%		
CAS: 26471-62-5 EINECS: 247-722-4 Index number: 615-006-00-4 Reg.nr.: 01-2119454791-34-XXXX	m-tolylidene diisocyanate Acute Tox. 2, H330; Resp. Sens. 1, H334; Carc. 2, H351; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335; Aquatic Chronic 3, H412, EUH204 Specific concentration limit: Resp. Sens. 1; H334: C ≥ 0.1 %	≥0.1-<1%		

(Contd. of page 3)

Safety data sheet complying with Regulation 1907/2006/EC (REACH Regulation), EU 2020/878 and Regulation No 1272/2008/EC (CLP)

Printing date 04.10.2021 Version number 3 (replaces version 2) Revision: 04.10.2021

Trade name: LAVA 20 CLEAR TOP COAT

Take affected persons out into the fresh air.

Seek immediate medical advice.

After inhalation:

In case of unconsciousness place patient stably in side position for transportation.

Supply fresh air and to be sure call for a doctor.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Remove contaminated clothing.

Wash contaminated clothing before use.

In case of skin irritation, consult a physician.

After eve contact:

Rinse opened eye for at least 15 minutes under running water.

Protect unharmed eye.

Seek immediate medical advice.

Avoid strong water jet-risk of cornea damage, consult a doctor.

After swallowing:

Do not induce vomiting; call for medical help immediately.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

May be fatal if swallowed and enters airways.

4.3 Indication of any immediate medical attention and special treatment needed

If swallowed or in case of vomiting, danger of entering the lungs.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents: CO2, powder or water spray. Fight larger fire with foam.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

Carbon dioxide (CO2)

Carbon monoxide (CO)

5.3 Advice for firefighters

Protective equipment:

Wear fully protective suit.

Mouth respiratory protective device.

Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Avoid inhalation of vapors.

Mouth respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

6.1.1 For non-emergency personnel Avoid contact with dripping or leaking material

6.1.2 For emergency responders

Wear protective equipment. Keep unprotected persons away.

(Contd. on page 5)

Printing date 04.10.2021

Version number 3 (replaces version 2)

Trade name: LAVA 20 CLEAR TOP COAT

(Contd. of page 4)

Revision: 04.10.2021

First-aid responders must wear protectice clothing, gloves, goggles and respiratory device with filter type A.

6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Do not allow to penetrate the ground/soil.

6.3 Methods and material for containment and cleaning up:

Collect with absorbent material (sand, diatomite).

Dispose contaminated material as waste according to item 13.

Send for recovery or disposal in suitable receptacles.

6.4 Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Open and handle receptacle with care.

Handle with care. Avoid jolting, friction and impact.

Information about fire - and explosion protection:





Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Do not spray onto a naked flame or any incandescent material.

Flammable gas-air mixtures may form in empty receptacles.

7.2 Conditions for safe storage, including any incompatibilities

Storage: Store in cool, dry conditions in well sealed receptacles.

Requirements to be met by storerooms and receptacles:

Store in a cool location.

Store away from sources of ignition

Prevent any seepage into the ground.

Provide ventilation for receptacles.

Further information about storage conditions: Protect from heat and direct sunlight.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

CAS: 108-65-6 2-methoxy-1-methylethyl acetate

WEL (Great Britain) Short-term value: 548 mg/m³, 100 ppm

Long-term value: 274 mg/m³, 50 ppm

Sk

IOELV (EU) Short-term value: 550 mg/m³, 100 ppm

Long-term value: 275 mg/m³, 50 ppm

Skin

(Contd. on page 6)

Printing date 04.10.2021

Version number 3 (replaces version 2)

Trade name: LAVA 20 CLEAR TOP COAT

(Contd. of page 5)

Revision: 04.10.2021

CAS: 4098-71-9 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

WEL (Great Britain) Short-term value: 0.07 mg/m³ Long-term value: 0.02 mg/m³

Sen; as -NCO

CAS: 108-31-6 maleic anhydride

WEL (Great Britain) Short-term value: 3 mg/m³ Long-term value: 1 mg/m³

Sen

DNELs

ETHYLBENZOLE REACTION MIXTURE, m-Xylol and p-Xylol.

DNEL Workers:

Inhalation - Intensive systemic effect = 289 mg/m 3

Inhalation - Chronic systemic effect = 77 mg/m 3

Skin - Chronic systemic effect = 180 mg / kg

DNEL Consumers:

Mouth - Chronic systemic effect = 1.6 mg / kg

Inhalation - Intensive systemic effect = 174 mg/m 3

Inhalation - Chronic systemic effect = 14.8 mg/m 3

Skin - Chronic systemic effect = 108 mg / kg

PNECs

ETHYLBENZOLE REACTION MIXTURE, m-Xylol and p-Xylol.

PNEC:

in fresh water 0.327 mg/1

in marine water 0,327 mg/1

for sediment in fresh water 12,46 mg/kg

for sediment in marinewater 12,46 mg / kg

for water, intermittent release of 0.327 mg/1

for STP 6.58 mg / 1 microorganisms

for the terrestrial area of 2,31 mg/kg

Ingredients with biological limit values:

CAS: 4098-71-9 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

BMGV (Great Britain) 1 µmol creatinine/mol

Medium: urine

Sampling time: At the end of the period od exposure

Parameter: isocyanate-derived diamine

8.2 Exposure controls

Individual protection measures, such as personal protective equipment General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

Do not breathe vapours or mists.

Do not eat, drink or smoke while using the product.

(Contd. on page 7)

Printing date 04.10.2021 Version number 3 (replaces version 2) Revision: 04.10.2021

Trade name: LAVA 20 CLEAR TOP COAT

(Contd. of page 6)

Respiratory protection:



Use suitable respiratory protective device in case of insufficient ventilation. Respiratory protection required in insufficiently ventilated working areas and during spraying. An air-fed mask, or for short periods of work, a combination of charcoal filter and particulate filter A2-P2 (EN529) is recommended.

Hand protection



Protective gloves resistant to chemicals (standard EN 374-1)

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Hand protection when handling the product at room temperature:

Butyl rubber - IIR: thickness ≥0,5mm; breakthrough time ≥480min.

Fluorinated rubber - FKM: thickness ≥0,4mm; breakthrough time ≥480min.

Recommendation: contaminated gloves should be disposed of.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

Eve/face protection



Safety glasses with side-shields (frame goggles) (e.g. EN 166)

Body protection:





Chemically resistant, protective work clothing (EN 14605) and boots.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state Viscous liquid

Colour: Clear Character Ch

Odour: Characteristic
Odour threshold: Not determined
Melting point/freezing point: Not determined

Boiling point or initial boiling point and boiling

range 162 °C

Flammability Not applicable

(Contd. on page 8)

Printing date 04.10.2021 Version number 3 (replaces version 2) Revision: 04.10.2021

Trade name: LAVA 20 CLEAR TOP COAT

(Contd. of page 7) Lower and upper explosion limit 0.7 Vol % Lower: 7.5 Vol % Upper: 30 °C Flash point: **Auto-ignition temperature:** Product is not selfigniting. **Decomposition temperature:** Not determined Viscosity: **Kinematic viscosity** Not determined **Kinematic viscosity** Dynamic at 20 °C: >40 mPas **Solubility** water: Not miscible Partition coefficient n-octanol/water (log value) Not determined Vapour pressure at 20 °C: 5 hPa Density and/or relative density Density at 20 °C: 1 g/cm³ Relative density Not determined Vapour density Not determined 9.2 Other information Appearance: Form: Liquid Important information on protection of health and environment, and on safety. **Auto-ignition temperature:** 315 °C **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible. Cloud point / clarification point: Oxidising properties Not considered as oxidising. **Evaporation rate** Not determined Information with regard to physical hazard classes **Explosives** Void Flammable gases Void Aerosols Void Oxidising gases Void Gases under pressure Void Flammable liquids Flammable liquid and vapour. Flammable solids Void Self-reactive substances and mixtures Void **Pyrophoric liquids** Void **Pyrophoric solids** Void **Self-heating substances and mixtures** Void Substances and mixtures, which emit flammable gases in contact with water Void **Oxidising liquids** Void **Oxidising solids** Void Organic peroxides Void Corrosive to metals Void

(Contd. on page 9)

Printing date 04.10.2021 Version number 3 (replaces version 2) Revision: 04.10.2021

Trade name: LAVA 20 CLEAR TOP COAT

(Contd. of page 8)

Desensitised explosives

Void

SECTION 10: Stability and reactivity

- 10.1 Reactivity Stable under normal conditions
- **10.2** Chemical stability Material is stable under normal conditions.

Thermal decomposition / conditions to be avoided

To avoid thermal decomposition do not overheat.

Stable at environment temperature.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- **10.4 Conditions to avoid** Avoid heat, sparkles, naked flame or other sources of ignition.
- 10.5 Incompatible materials No further relevant information available.
- **10.6 Hazardous decomposition products** No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Dermal	LD50	3,508 mg/kg
Inhalative	LC50/4 h (vapour)	33.3 mg/l

Reaction mass of ethylbenzene and m-xylene and p-xylene

Oral	LD50	4,300 mg/kg (rat)
Inhalative	LC50 (4h)	5,000 ppm (rat)
		5,000 ppm (rabbit)

CAS: 108-65-6 2-methoxy-1-methylethyl acetate

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rat)
Inhalative	LC50 (4h)	1,805.05 ppm (rat)

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/irritation Causes serious eye irritation.

Respiratory or skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure

The product is classified as Specific Target Organ Toxicity after single exposure Category 3

May cause respiratory irritation.

STOT-repeated exposure

STOT Repeated Exposure Category 2

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

The product is classified Aspiration toxicity Category 1

May be fatal if swallowed and enters airways.

(Contd. on page 10)

Printing date 04.10.2021

Version number 3 (replaces version 2)

(Contd. of page 9)

Revision: 04.10.2021

Trade name: LAVA 20 CLEAR TOP COAT

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

CAS: 108-65-6 2-methoxy-1-methylethyl acetate

EC50 (48h) 8.8 mg/l (crustacean)

LC50 (96h) 6.83 mg/l (fis)

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable. **vPvB:** Not applicable.

12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.

12.7 Other adverse effects

Remark: Harmful to fish

Additional ecological information:

General notes:

The product contains materials that are harmful to the environment.

Harmful to aquatic organisms

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation



Dispose according to National Regulations.



Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact manufacturer for recycling information.

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN number or ID number

ADR, IMDG, IATA UN1866

(Contd. on page 11)

Printing date 04.10.2021 Version number 3 (replaces version 2) Revision: 04.10.2021

Trade name: LAVA 20 CLEAR TOP COAT

(Contd. of page 10)

14.2 UN proper shipping name

ADR 1866 RESIN SOLUTION IMDG, IATA RESIN SOLUTION

14.3 Transport hazard class(es)

ADR, IMDG, IATA



Class 3 Flammable liquids.

Label 3

14.4 Packing group
ADR, IMDG, IATA

14.5 Environmental hazards:

Marine pollutant: No

14.6 Special precautions for user Warning: Flammable liquids.

Hazard identification number (Kemler code): 30
EMS Number: F-E,S-E
Stowage Category A

14.7 Maritime transport in bulk according to IMO

instruments Not applicable.

Transport/Additional information:

ADR

Limited quantities (LQ) 5L Excepted quantities (EQ) 5Code: E1

> Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

Transport category 3 **Tunnel restriction code** D/E

IMDG

Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1

> Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

UN "Model Regulation": UN 1866 RESIN SOLUTION, 3, III

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 94/62/EC on packaging and packaging waste.

REACH Regulation 1907/2006/EC

Regulation (EU) 2020/878

CLP Regulation 1272/2008/EC

(Contd. on page 12)

Printing date 04.10.2021 Version number 3 (replaces version 2) Revision: 04.10.2021

Trade name: LAVA 20 CLEAR TOP COAT

(Contd. of page 11)

Directive 98/24/EC on the protection of health and safety of workers from the risks related to chemicals agents at work.

Council Directive 94/33/EC on the protection of young people at work, as ammended.

Directive 92/85/EEC on the introduction of measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding, as ammended

Directive 2012/18/EU

Named dangerous substances - ANNEX I Substance is not listed.

Seveso category

P5c FLAMMABLE LIQUIDS P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 74

National regulations:

Other regulations, limitations and prohibitive regulations

Substances of very high concern (SVHC) according to REACH, Article 57

It doesn't contain substances of very high concern (SVHC).

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H331 Toxic if inhaled.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

EUH204 Contains isocyanates. May produce an allergic reaction.

Training hints

Suitable training on safety in handling, storing and converting the product should be given to the employees based on all the existing information.

(Contd. on page 13)

Printing date 04.10.2021 Version number 3 (replaces version 2) Revision: 04.10.2021

Trade name: LAVA 20 CLEAR TOP COAT

(Contd. of page 12)

Department issuing SDS:



OWL WATERPROOFING SOLUTIONS

135, Slaney Road, Dublin Industrial Estate

Glasnevin, Dublin 11 Tel: +353 01 830 2250

Email: info@owlwaterproofing.co.uk Website: www.owlwaterproofing.co.uk

Version number of previous version: 2

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the

International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids - Category 2

Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 4: Acute toxicity – Category 4 Acute Tox. 3: Acute toxicity – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation - Category 1

Skin Sens. 1B: Skin sensitisation - Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* Data compared to the previous version altered.