Revision: 17.09.2021



OWL PU MASTIC

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its Amendment Regulation (EC) No.1272/2008 (CLP) and EU 2020/878

Printing date 17.09.2021

Version number 2 (replaces version 1)

SECTION 1: Identification of the substance/mixture and of the company /undertaking

1.1 Product identifier

Trade name: OWL PU MASTIC

1.2 Relevant identified uses of the substance or mixture and uses advised against Professional use **Application of the substance / the mixture:** Polyourethane sealant for movement joints.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

OWL WATERPROOFING SOLUTIONS

135 Slaney Road, Dublin Industrial Estate

Glasnevin, Dublin 11 Tel: +353 01 830 2250

Email: info@owlwaterproofing.co.uk Website: www.owlwaterproofing.co.uk **1.4 Emergency telephone number:**



European Emergency Tel.: +353 01 830 2250

SECTION 2: Hazard identification

2.1 Classification of the substance or mixture

Classification according to Regulation EC No 1272/2008 CLP:



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

2.2 Label elements

Labelling according to Regulation EC No 1272/2008 CLP:

The product is classified and labelled according to the CLP regulation.

Hazard pictograms:



GHS07

Signal word: Warning

Hazard statements:

H315 Causes skin irritation.

H319 Causes serious eye irritation.

Precautionary statements

P264

Wash thoroughly after handling.

(Contd. on page 2)

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its Amendment Regulation (EC) No.1272/2008 (CLP) and EU 2020/878

Printing date 17.09.2021 Version number 2 (replaces version 1) Revision: 17.09.2021

Trade name: OWL PU MASTIC

(Contd. of page 1)

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P302+P352 IF ON SKIN: Wash with plenty of water and soap.

P321 Specific treatment (see on this label).

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P332+P313 If skin irritation occurs: Get medical advice/attention.

Additional information:

EUH204 Contains isocyanates. May produce an allergic reaction.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable. **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture: consisting of the following components.

Ingredients according Regulation	(EU) 2020/878:	
CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 Reg.nr.: 01-2119488216-32-XXXX	xylene Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	≤10%
CAS: 100-41-4 EINECS: 202-849-4 Index number: 601-023-00-4 Reg.nr.: 01-2119489370-35-XXXX	ethylbenzene Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332	≤5%
CAS: 2530-83-8 EINECS: 219-784-2	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane Eye Dam. 1, H318	≤1%
CAS: 64742-47-8 EINECS: 265-149-8 Index number: 649-422-00-2	Distillates (petroleum), hydro- treated light Asp. Tox. 1, H304	≤1%
CAS: 101-68-8 EINECS: 202-966-0 Index number: 615-005-00-9 Reg.nr.: 01-2119457014-47-XXXX	4,4'-methylenediphenyl diisocyanate Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; ↑ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5 % Skin Irrit. 2; H315: C ≥ 5 % Resp. Sens. 1; H334: C ≥ 0.1 % STOT SE 3; H335: C ≥ 5 %	≥0.01-<0.1%

(Contd. on page 3)

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its Amendment Regulation (EC) No.1272/2008 (CLP) and EU 2020/878

Printing date 17.09.2021 Version number 2 (replaces version 1) Revision: 17.09.2021

Trade name: OWL PU MASTIC

(Contd. of page 2)

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

Allow affected people to get some fresh air.

Request medical help immediately

After inhalation:

If the patient becomes unconscious, secure him in a side position for transportation.

Get fresh air.

If symptoms last, see a doctor.

After skin contact:

Wash with soap and water immediately, then thoroughly rinse.

Talk to a doctor if skin irritation persists.

After eye contact:

Rinse the opened eye under flowing water for at least 15 minutes.

Take off your contact lenses and keep rinsing for a few minutes.

Consult a doctor if the symptoms continue.

Safeguard uninjured eye.

After swallowing:

Do not force yourself to vomit; instead, contact emergency help right away.

Ensure you are getting lots of fresh air and drink. Make a doctor's appointment immediately.

Seek emergency medical attention.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

5.3 Advice for firefighters

Protective equipment:

In the event of fire, self-contained breathing gear and full protective clothes are required.

Additional information

Separately collect contaminated fire-fighting water. It should not go down the sewage line.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Make sure there is enough air circulation.

Avoid breathing in fumes.

Stay away from sources of ignition.

Wear safety gear when necessary. Keep vulnerable people at a distance.

Put on safety gear. Avoid skin and eye contact.

6.1.1 For non-emergency personnel Stay away from any leaking or flowing substances.

(Contd. on page 4)

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its Amendment Regulation (EC) No.1272/2008 (CLP) and EU 2020/878

Printing date 17.09.2021

Version number 2 (replaces version 1)

Trade name: OWL PU MASTIC

(Contd. of page 3)

Revision: 17.09.2021

6.1.2 For emergency responders

Protective gear, gloves, goggles, and a breathing device with a type A filter are required for first-aid rescuers.

6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Do not allow to penetrate the ground/soil.

6.3 Methods and material for containment and cleaning up:

Utilize absorbent material to collect (sand, diatomite).

Make sure there is enough airflow.

Utilize a liquid binding substance to absorb liquid components.

6.4 Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

If applied effectively, no further safety measures are required.

Assure enough exhaustion and airflow at the worksite.

Avoid inhaling vapors.

Avoid eating, drinking, and smoking while using the product.

Avoid skin and eye contact.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Preserve the container tightly locked.

To avoid leaks, keep containers firmly in place and upright.

Requirements to be met by storerooms and receptacles:

Retain in a cold environment.

Don't let any liquid soak into the ground.

Receptacles should have ventilation.

Information about storage in one common storage facility:

Keep away from food.

Keep away from water.

Further information about storage conditions: Prevent exposure to heat and sunshine.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

CAS: 1330-20-7 xylene

WEL (Great Britain) Short-term value: 441 mg/m³, 100 ppm

Long-term value: 220 mg/m³, 50 ppm

Sk; BMGV

IOELV (EU) | Short-term value: 442 mg/m³, 100 ppm

Long-term value: 221 mg/m³, 50 ppm

Skin

(Contd. on page 5)

Revision: 17.09.2021

OWL PU MASTIC

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its Amendment Regulation (EC) No.1272/2008 (CLP) and EU 2020/878

Printing date 17.09.2021

Version number 2 (replaces version 1)

Trade name: OWL PU MASTIC

CAS: 100-41-4 ethylbenzene

WEL (Great Britain) Short-term value: 552 mg/m³, 125 ppm
Long-term value: 441 mg/m³, 100 ppm
Sk

IOELV (EU) Short-term value: 884 mg/m³, 200 ppm
Long-term value: 442 mg/m³, 100 ppm
Skin

CAS: 101-68-8 4,4'-methylenediphenyl diisocyanate

WEL (Great Britain) Short-term value: 0.07 mg/m³
Long-term value: 0.02 mg/m³
Sen; as -NCO

DNELs

CAS: 1330-20-7 Xylene (mixture of isomers)

Workers:

High Exposure, Systemic, 180 mg/kg

Inhalation, Short Term Exposure, Systemic, 289 mg/m³ Inhalation, Short Term Exposure, Local, 289 mg/m³ Inhalation, Large exposure, Systemic, 77 mg/m³

Consumers:

Oral, Large exposure, Systemic, 1.6 mg/kg Demal, Large exposure, Systemic, 108 mg/kg Inhalation, Large Exposure, Systemic,14.8 mg/m³

CAS: 100-41-4 Ethylbenzene

Workers:

Dermal-Large exposure-Systemic-180 mg/kg Inhalation-Short-term exposure-Local-293 mg/m³ Inhalation - Large exposure - Systemic - 77 mg/m³

Consumers:

Oral Exposure-Large Systemic-1.6 mg/kg Inhalation-Large exposure-Systemic-15 mg/m³ CAS: 101-68-8 4,4'-methylenediphenyl diisocyanate.

Workers:

Inhalation - long-term systemic & local effects: 0.05 mg/m³.

Inhalation - acute systemic & local effects: 0.1 mg/m³.

Dermal - acute systemic effects: 50 mg/kg bw/d.

Dermal - acute local effects: 28.7 mg/cm²

Consumers:

Inhalation - long-term systemic & local effects: 0.025 mg/m³.

Inhalation - acute systemic & local effects: 0.05 mg/m³.

Dermal - acute systemic effects: 25 mg/kg bw/d.

Dermal - acute local effects: 17.2 mg/cm² Oral - acute local effects: 20 mg/kg bw/d.

PNECs

CAS: 1330-20-7 Xylene (mixture of isomers)

STP: 6.58 mg/l

Freshwater: 0.327 mg/l Soil: 2.31 mg/kg

(Contd. on page 6)

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its Amendment Regulation (EC) No.1272/2008 (CLP) and EU 2020/878

Printing date 17.09.2021

Version number 2 (replaces version 1)

Trade name: OWL PU MASTIC

(Contd. of page 5)

Revision: 17.09.2021

Marine water: 0.327 mg/l Intermittent releases: 0.327 mg/l Sediment (freshwater): 12.46 mg/kg Sediment (marinewater): 12.46 mg/kg

CAS: 100-41-4 Ethylbenzene

STP 9.6 mg/L Freshwater: 0.1 mg/l Soil 2,68 mg/kg Marine water: 0.01 mg/l Intermittent releases: 0.1 mg/l Sediment (freshwater): 13.7 mg/kg For oral use: 20 g/kg

Sediment (marinewater): 1.37 mg/kg

CAS: 101-68-8 4,4'-methylenediphenyl diisocyanate.

Fresh water: > 1 mg/l Marine water: > 0.1 mg/l Sewage treatment plant: > 1 mg/l Soil: >1 mg/kg dry weight.

8.2 Exposure controls

8.2.1. Appropriate engineering controls

Make sure there is enough airflow.

Take the necessary safety precautions while handling chemicals and mixtures.

Individual protection measures, such as personal protective equipment General protective and hygienic measures:

Avoid food, drink, and feed.

Prior to breaks and after work, wash your hands.

Keep your hands away from your skin and eyes.

Avoid eating, drinking, and smoking while using the product.

Avoid inhaling mists or vapors.

Respiratory protection:



In cases of inadequate ventilation, use an appropriate respiratory protection gear. Respiratory protection is necessary while spraying and in poorly ventilated work spaces. For brief durations of labor, a charcoal filter and particle filter A2-P2 (EN529) combination mask or an air-fed mask are advised.

Hand protection



Protective gloves resistant to chemicals (standard EN 374-1)

The material used for the gloves must be waterproof and resistant to the product, substance, or preparation. No advice for the glove material for the product, preparation, or chemical mixture can be made due to a lack of studies. Choose the glove material while taking the degradation, diffusion, and penetration rates into account

Material of gloves

Hand protection when handling the product at room temperature:

Butyl rubber - IIR: thickness ≥0,5mm; breakthrough time ≥480min.

Fluorinated rubber - FKM: thickness ≥0,4mm; breakthrough time ≥480min.

Recommendation: contaminated gloves should be disposed of.

(Contd. on page 7)

Page 7/12

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its Amendment Regulation (EC) No.1272/2008 (CLP) and EU 2020/878

Printing date 17.09.2021 Version number 2 (replaces version 1) Revision: 17.09.2021

Trade name: OWL PU MASTIC

(Contd. of page 6)

Penetration time of glove material

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

Eye/face protection



Safety glasses with side-shields (frame goggles) (e.g. EN 166)

Body protection:





Chemically resistant, protective work clothing (EN 14605) and boots.

Environmental exposure controls

Prevent enter of the product into drains, surface and groundwater and soil. Dispose of flushing liquids in accordance with local and national regulations.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state Liquid

Colour:Various coloursOdour:CharacteristicOdour threshold:Not determinedMelting point/freezing point:Not determinedFlammabilityNot applicable

Lower and upper explosion limit

Lower:Not determinedUpper:Not determinedFlash point:Not Flammable

Auto-ignition temperature: Product is not selfigniting.

Decomposition temperature: pHNot determined
Not determined

Viscosity:

Kinematic viscosity Not determined

Kinematic viscosity

Dynamic: Not determined

Solubility

water: Insoluble
Partition coefficient n-octanol/water (log value)
Vapour pressure: Not determined
Not determined

Density and/or relative density

Density at 20 °C:1.12-1.18 g/cm³Relative densityNot determinedVapour densityNot determined

(Contd. on page 8)

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its Amendment Regulation (EC) No.1272/2008 (CLP) and EU 2020/878

Printing date 17.09.2021 Version number 2 (replaces version 1) Revision: 17.09.2021

Trade name: OWL PU MASTIC

(Contd. of page 7)

9.2 Other information

Appearance:

Explosives

Form: Paste

Important information on protection of health and

environment, and on safety.

Auto-ignition temperature: Not determined

Explosive properties: Product does not present an explosion hazard.

Void

Cloud point / clarification point:

Oxidising properties Not oxidising
Evaporation rate Not determined

Information with regard to physical hazard classes

Flammable gases Void Aerosols Void Void Oxidising gases Gases under pressure Void Flammable liquids Void Flammable solids Void **Self-reactive substances and mixtures** Void **Pyrophoric liquids** Void **Pyrophoric solids** Void Self-heating substances and mixtures Void Substances and mixtures, which emit flammable gases in contact with water Void **Oxidising liquids** Void **Oxidising solids** Void Organic peroxides Void Corrosive to metals Void **Desensitised explosives** Void

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided Stable at environment temperature.

10.3 Possibility of hazardous reactions No dangerous reactions known.

10.4 Conditions to avoid Avoid heat, sparkles, naked flame or other sources of ignition.

10.5 Incompatible materials Amines

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Dermal LD50 ≥17,000 mg/kg	(rabbit)
---------------------------	----------

Inhalative LC50/4 h (vapour) ≥73.3 mg/l

(Contd. on page 9)

Revision: 17.09.2021

OWL PU MASTIC

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its Amendment Regulation (EC) No.1272/2008 (CLP) and EU 2020/878

Printing date 17.09.2021

Version number 2 (replaces version 1)

Trade name: OWL PU MASTIC

		(Contd. of page 8)
CAS: 1330	0-20-7 xylene	
Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	1,700 mg/kg (rabbit)
Inhalative	LC50 (4h)	5,000 ppm (rat)
CAS: 100-41-4 ethylbenzene		
Oral	LD50	3,500 mg/kg (rat)
Dermal	LD50	17,800 mg/kg (rabbit)
Inhalative	LC50 (4h)	4,000 ppm (rat)
CAS: 101-	CAS: 101-68-8 4,4'-methylenediphenyl diisocyanate	
Oral	LD50	2,200 mg/kg (rat)
Dermal	LD50	>9,400 mg/kg (rabbit)

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/irritation Causes serious eye irritation.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

Additional toxicological information:

Repeated dose toxicity Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12:	Ecological	linformation
--------------------	-------------------	--------------

12.1 Toxicity	
---------------	--

1201 101110103			
Aquatic toxici	ity:		
CAS: 1330-20	CAS: 1330-20-7 xylene		
EC50 (48h)	>7.4 mg/l (daphnia magna)		
LC50 (96h)	2.6 mg/l (fis)		
NOEC r (72h)	440 mg/l (algae)		
CAS: 100-41-4 ethylbenzene			
EC50 (48h)	73 mg/l (daphnia magna)		
CAS: 101-68-8 4,4'-methylenediphenyl diisocyanate			
EC50	>1,000 mg/l (daphnia magna) (Daphnia magna Reproduction Test)		
EC50 (72h)	>1,640 mg/l (ssu) (Freshwater Alga and Cyanobacteria, Grow Inhibition)		
LC50 (96h)	>1,000 mg/l (Danio rerio) (Fish, Acute Toxicity Test)		
NOEC (21d)	>10 mg/l (Daphnia magna) (Daphnia sp. Acute Immobilisation Test)		

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

(Contd. on page 10)

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its Amendment Regulation (EC) No.1272/2008 (CLP) and EU 2020/878

Printing date 17.09.2021

Version number 2 (replaces version 1)

Trade name: OWL PU MASTIC

(Contd. of page 9)

Revision: 17.09.2021

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable. **vPvB:** Not applicable.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation



Dispose according to National Regulations.



Not to be disposed of with regular trash. Do not let product enter the drainage system.

Uncleaned packaging:

Recommendation: Official guidelines must be followed while disposing of materials.

SECTION 14: Transport information		
14.1 UN number or ID number ADR, ADN, IMDG, IATA	Void	
14.2 UN proper shipping name ADR, ADN, IMDG, IATA	Void	
14.3 Transport hazard class(es)		
ADR, ADN, IMDG, IATA Class	Void	
14.4 Packing group ADR, IMDG, IATA	Void	
14.5 Environmental hazards:	Not applicable.	
14.6 Special precautions for user	Not applicable.	
14.7 Maritime transport in bulk according instruments	g to IMO Not applicable.	
UN "Model Regulation":	Void	

(Contd. on page 11)

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its Amendment Regulation (EC) No.1272/2008 (CLP) and EU 2020/878

Printing date 17.09.2021 Version number 2 (replaces version 1) Revision: 17.09.2021

Trade name: OWL PU MASTIC

(Contd. of page 10)

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH Regulation 1907/2006/EC

Regulation (EU) 2020/878

CLP Regulation 1272/2008/EC

Directive 98/24/EC on safeguarding employees' health and safety against hazards posed by chemical agents at work.

Youth protection at work: amended version of Council Directive 94/33/EC.

The amended version of Directive 92/85/EEC on the adoption of measures to promote advancements in the safety and health at work of pregnant employees, new mothers, and nursing employees

Directive 2012/18/EU

Named dangerous substances - ANNEX I Substance is not listed.

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 56a, 74

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

National regulations:

Other regulations, limitations and prohibitive regulations

Substances of very high concern (SVHC) according to REACH, Article 57

It doesn't contain substances of very high concern (SVHC).

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on what we know right now. This, however, does not create a legally binding business relationship or a guarantee for any particular product characteristics.

Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.

(Contd. on page 12)

Page 12/12

Safety Data Sheet

According to Regulation (EC) No. 1907/2006 (REACH) with its Amendment Regulation (EC) No.1272/2008 (CLP) and EU 2020/878

Printing date 17.09.2021

Version number 2 (replaces version 1)

Trade name: OWL PU MASTIC

(Contd. of page 11)

Revision: 17.09.2021

H351 Suspected of causing cancer.

May cause damage to organs through prolonged or repeated exposure. H373

EUH204 Contains isocyanates. May produce an allergic reaction.

Training hints

On the basis of all the available knowledge, the staff should receive the proper training about safety when handling, storing, and converting the product.

Department issuing SDS:



OWL WATERPROOFING SOLUTIONS

135 Slaney Road, Dublin Industrial Estate

Glasnevin, Dublin 11 Tel: +353 01 830 2250

Email: info@owlwaterproofing.co.uk Website: www.owlwaterproofing.co.uk

Version number of previous version: 1

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the

International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids - Category 2

Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Resp. Sens. 1: Respiratory sensitisation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1

Carc. 2: Carcinogenicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

* Data compared to the previous version altered.